

Surface mounted downlight for compact fluorescent lamps. Body is made of aluminium (standard white – available in any RAL colour on request).



DLN 255 with plain glossy reflector.

Technical extras upon request:

1. Emergency supply  
- battery pack 1/2/3h (please add EM1, EM2 or EM3 after index number)
2. Compensation or passive power (capacitor).  
Please add COMPENSATION after index number.
3. Dimmable ballast EVG DIM (1-10 V).  
Please add EVG DIM after index number.
4. Digital dimmable ballast (DALI).  
Please add DALI after index number.

IP20

230 V  
50 Hz



CE



Diamond faceted reflector.

Index no.	Lamp	Weight	Socket
DLN 255 with faceted reflector.			
F27.255.2266V	VVG, 1x18W TC-D	2,10 kg	G24d - 2
F27.255.2266E	EVG, 1x18W TC-DEL	1,90 kg	G24q - 2
F27.255.2267V	VVG, 1x26W TC-D	2,20 kg	G24d - 3
F27.255.2267E	EVG, 1x26W TC-DEL	1,95 kg	G24q - 3
F27.255.2268V	VVG, 2x18W TC-D	2,30 kg	G24d - 2
F27.255.2268E	EVG, 2x18W TC-DEL	2,00 kg	G24q - 2
F27.255.2269V	VVG, 2x26W TC-D	2,40 kg	G24d - 3
F27.255.2269E	EVG, 2x26W TC-DEL	2,00 kg	G24q - 3

Index no.	Lamp	Weight	Socket
DLN 255 with plain glossy reflector.			
G27.255.2266V	VVG, 1x18W TC-D	2,10 kg	G24d - 2
G27.255.2266E	EVG, 1x18W TC-DEL	1,90 kg	G24q - 2
G27.255.2267V	VVG, 1x26W TC-D	2,20 kg	G24d - 3
G27.255.2267E	EVG, 1x26W TC-DEL	1,95 kg	G24q - 3
G27.255.2268V	VVG, 2x18W TC-D	2,30 kg	G24d - 2
G27.255.2268E	EVG, 2x18W TC-DEL	2,00 kg	G24q - 2
G27.255.2269V	VVG, 2x26W TC-D	2,40 kg	G24d - 3
G27.255.2269E	EVG, 2x26W TC-DEL	2,00 kg	G24q - 3

For decorative accessories see page 240.

