


DL 100 FORTIMO SLM

Recessed LED luminaire. Body is made of steel and aluminium and it is available in all RAL colours. Light source - Philips Fortimo SLM or Osram PrevaLED module. Standard EVG ballast, Touch DALI version on request.



IP20

230 V
50 Hz



CE

High quality, energy efficient white LED light with CRI 80 and more. Applications:

- Retail: shop windows, wall - washing, accent and display lighting
- Hospitality: lobbies, reception areas, restaurants, bars, elevators
- Recreation: museums, galleries, theatres and other public places



Index no.	Lumen output	Wattage	System efficacy	Colour temp.	Colour rendering index	Lifetime	Weight
0000-003665.1100/830	1100 lm	14W	69 lm/W	3000K	85 Ra	50,000 h	0,96 kg
0000-003665.1100/835	1100 lm	13W	74 lm/W	3500K	85 Ra	50,000 h	0,96 kg
0000-003665.1100/840	1100 lm	12W	80 lm/W	4000K	85 Ra	50,000 h	0,96 kg
0000-003665.2000/827	2000 lm	26W	69 lm/W	2700K	85 Ra	50,000 h	0,96 kg
0000-003665.2000/830	2000 lm	24W	74 lm/W	3000K	85 Ra	50,000 h	0,96 kg
0000-003665.2000/835	2000 lm	23W	77 lm/W	3500K	85 Ra	50,000 h	0,96 kg
0000-003665.2000/840	2000 lm	20W	86 lm/W	4000K	85 Ra	50,000 h	0,96 kg
0000-003665.2000/827	2000 lm	35W	52 lm/W	2700K	95 Ra	50,000 h	0,96 kg
0000-003665.2000/830	2000 lm	32W	57 lm/W	3000K	95 Ra	50,000 h	0,96 kg
0000-003665.3000/827	3000 lm	42W	64 lm/W	2700K	85 Ra	50,000 h	0,96 kg
0000-003665.3000/830	3000 lm	39W	69 lm/W	3000K	85 Ra	50,000 h	0,96 kg
0000-003665.3000/835	3000 lm	40W	68 lm/W	3500K	85 Ra	50,000 h	0,96 kg
0000-003665.3000/840	3000 lm	36W	75 lm/W	4000K	85 Ra	50,000 h	0,96 kg

Touch & DALI ballast is also available - please add TD after index no.

