

Recessed adjustable LED luminaire. Body is made of steel and aluminium and it is available in all RAL colours. Light source - Philips Fortimo SLM or Osram PrevaLED module. Standard EVG ballast, Touch DALI version on request.



High quality, energy efficient white LED light with CRI 80 and more.



Applications:

- Retail: shop windows, wall - washing, accent and display lighting
- Hospitality: lobbies, reception areas, restaurants, bars, elevators
- Recreation: museums, galleries, theatres and other public places



Index no.	Lumen output	Wattage	System efficacy	Colour temp.	Colour rendering index	Lifetime	Weight
0000-003072.41100/830	4x1100 lm	4x14W	69 lm/W	3000K	85 Ra	50,000 h	7,80 kg
0000-003072.41100/835	4x1100 lm	4x13W	74 lm/W	3500K	85 Ra	50,000 h	7,80 kg
0000-003072.41100/840	4x1100 lm	4x12W	80 lm/W	4000K	85 Ra	50,000 h	7,80 kg
0000-003072.42000/827	4x2000 lm	4x26W	69 lm/W	2700K	85 Ra	50,000 h	7,80 kg
0000-003072.42000/830	4x2000 lm	4x24W	74 lm/W	3000K	85 Ra	50,000 h	7,80 kg
0000-003072.42000/835	4x2000 lm	4x23W	77 lm/W	3500K	85 Ra	50,000 h	7,80 kg
0000-003072.42000/840	4x2000 lm	4x20W	86 lm/W	4000K	85 Ra	50,000 h	7,80 kg
0000-003072.42000/927	4x2000 lm	4x35W	52 lm/W	2700K	95 Ra	50,000 h	7,80 kg
0000-003072.42000/930	4x2000 lm	4x32W	57 lm/W	3000K	95 Ra	50,000 h	7,80 kg
0000-003072.43000/827	4x3000 lm	4x42W	64 lm/W	2700K	85 Ra	50,000 h	7,80 kg
0000-003072.43000/830	4x3000 lm	4x39W	69 lm/W	3000K	85 Ra	50,000 h	7,80 kg
0000-003072.43000/835	4x3000 lm	4x40W	68 lm/W	3500K	85 Ra	50,000 h	7,80 kg
0000-003072.43000/840	4x3000 lm	4x36W	75 lm/W	4000K	85 Ra	50,000 h	7,80 kg

Touch & DALI ballast is also available - please add TD after index no.



255 x 255