

Recessed adjustable LED luminaire. Body is made of steel and aluminium and it is available in all RAL colours. Light source - Philips Fortimo SLM or Osram PrevaLED module. Standard EVG ballast, Touch DALI version on request.

High quality, energy efficient white LED light with CRI 80 and more.

Applications:

- Retail: shop windows, wall - washing, accent and display lighting
- Hospitality: lobbies, reception areas, restaurants, bars, elevators
- Recreation: museums, galleries, theatres and other public places



- IP20
- 230 V
50 Hz
- F
- ⊥
- €



Index no.	Lumen output	Wattage	System efficacy	Colour temp.	Colour rendering index	Lifetime	Weight
0000-003049.31100/830	3x1100 lm	3x14W	69 lm/W	3000K	85 Ra	50,000 h	6,10 kg
0000-003049.31100/835	3x1100 lm	3x13W	74 lm/W	3500K	85 Ra	50,000 h	6,10 kg
0000-003049.31100/840	3x1100 lm	3x12W	80 lm/W	4000K	85 Ra	50,000 h	6,10 kg
0000-003049.32000/827	3x2000 lm	3x26W	69 lm/W	2700K	85 Ra	50,000 h	6,10 kg
0000-003049.32000/830	3x2000 lm	3x24W	74 lm/W	3000K	85 Ra	50,000 h	6,10 kg
0000-003049.32000/835	3x2000 lm	3x23W	77 lm/W	3500K	85 Ra	50,000 h	6,10 kg
0000-003049.32000/840	3x2000 lm	3x20W	86 lm/W	4000K	85 Ra	50,000 h	6,10 kg
0000-003049.32000/927	3x2000 lm	3x35W	52 lm/W	2700K	95 Ra	50,000 h	6,10 kg
0000-003049.32000/930	3x2000 lm	3x32W	57 lm/W	3000K	95 Ra	50,000 h	6,10 kg
0000-003049.33000/827	3x3000 lm	3x42W	64 lm/W	2700K	85 Ra	50,000 h	6,10 kg
0000-003049.33000/830	3x3000 lm	3x39W	69 lm/W	3000K	85 Ra	50,000 h	6,10 kg
0000-003049.33000/835	3x3000 lm	3x40W	68 lm/W	3500K	85 Ra	50,000 h	6,10 kg
0000-003049.33000/840	3x3000 lm	3x36W	75 lm/W	4000K	85 Ra	50,000 h	6,10 kg

Touch & DALI ballast is also available - please add TD after index no.

