

Recessed adjustable LED luminaire. Body is made of steel and aluminium and it is available in all RAL colours. Light source - Philips Fortimo LED DLM or Fortimo Food module. Standard EVG ballast, Touch DALI version on request. This LED downlight is also available with 3 hour emergency unit.



IP20

230 V
50 Hz



CE

High quality, energy efficient white LED light with CRI 80.



Perfect replacement for CFL downlights in:

- Offices
- Public buildings
- Hotel lobbies and receptions
- Retail
- Supermarkets



Index no.	Lumen output	Wattage	System efficacy	Colour temp.	Colour rendering index	Lifetime	Weight
0000-003058.1100/830	1100 lm	12W	75 lm/W	3000K	80 Ra	50,000 h	3,30 kg
0000-003058.1100/840	1100 lm	11W	82 lm/W	4000K	80 Ra	50,000 h	3,30 kg
0000-003058.2000/830	2000 lm	22W	78 lm/W	3000K	80 Ra	50,000 h	3,30 kg
0000-003058.2000/840	2000 lm	20W	86 lm/W	4000K	80 Ra	50,000 h	3,30 kg
0000-003058.3000/830	3000 lm	34W	77 lm/W	3000K	80 Ra	50,000 h	3,30 kg
0000-003058.3000/840	3000 lm	32W	82 lm/W	4000K	80 Ra	50,000 h	3,30 kg
0000-003058.1800/830/F	1800 lm	30W	53 lm/W	3000K	75 Ra	50,000 h	3,30 kg
0000-003058.2000/840/F	2000 lm	32W	55 lm/W	4000K	75 Ra	50,000 h	3,30 kg
0000-003058.3000/830/F	2700 lm	43W	65 lm/W	3000K	75 Ra	50,000 h	3,30 kg
0000-003058.3000/840/F	2700 lm	41W	75 lm/W	4000K	75 Ra	50,000 h	3,30 kg

Touch & DALI ballast is also available - please add TD after index no. Last four items are with Fortimo Food modules.



190