

Pendent adjustable LED luminaire. Body is made of steel and aluminium and it is available in all RAL colours. Light source - Philips Fortimo SLM or Osram PrevaLED module. Standard EVG ballast, Touch DALI version on request. Suspension set - 1,5 meter.



High quality, energy efficient white LED light with CRI 80 and more.

Applications:

- Retail: shop windows, wall - washing, accent and display lighting
- Hospitality: lobbies, reception areas, restaurants, bars, elevators
- Recreation: museums, galleries, theatres and other public places

- IP20
- 230 V  
50 Hz
- F
- ⏚
- CE



Index no.	Lumen output	Wattage	System efficacy	Colour temp.	Colour rendering index	Lifetime	Weight
0000-003372.21100/830	2x1100 lm	2x14W	69 lm/W	3000K	85 Ra	50,000 h	4,73 kg
0000-003372.21100/835	2x1100 lm	2x13W	74 lm/W	3500K	85 Ra	50,000 h	4,73 kg
0000-003372.21100/840	2x1100 lm	2x12W	80 lm/W	4000K	85 Ra	50,000 h	4,73 kg
0000-003372.22000/827	2x2000 lm	2x26W	69 lm/W	2700K	85 Ra	50,000 h	4,73 kg
0000-003372.22000/830	2x2000 lm	2x24W	74 lm/W	3000K	85 Ra	50,000 h	4,73 kg
0000-003372.22000/835	2x2000 lm	2x23W	77 lm/W	3500K	85 Ra	50,000 h	4,73 kg
0000-003372.22000/840	2x2000 lm	2x20W	86 lm/W	4000K	85 Ra	50,000 h	4,73 kg
0000-003372.22000/927	2x2000 lm	2x35W	52 lm/W	2700K	95 Ra	50,000 h	4,73 kg
0000-003372.22000/930	2x2000 lm	2x32W	57 lm/W	3000K	95 Ra	50,000 h	4,73 kg
0000-003372.23000/827	2x3000 lm	2x42W	64 lm/W	2700K	85 Ra	50,000 h	4,73 kg
0000-003372.23000/830	2x3000 lm	2x39W	69 lm/W	3000K	85 Ra	50,000 h	4,73 kg
0000-003372.23000/835	2x3000 lm	2x40W	68 lm/W	3500K	85 Ra	50,000 h	4,73 kg
0000-003372.23000/840	2x3000 lm	2x36W	75 lm/W	4000K	85 Ra	50,000 h	4,73 kg

Touch & DALI ballast is also available - please add TD after index no.

