



DL 220 SOIL FORTIMO DLM

Recessed IP54 LED luminaire. Body is made of aluminium and it is available in all RAL colours. Light source - Philips Fortimo LED DLM module. Standard EVG ballast, Touch DALI version on request. This LED downlight is also available with 3 hour emergency unit.

- IP54
- 230 V
50 Hz
- F
- ⊕
- CE



Index no.	Lumen output	Wattage	System efficacy	Colour temp.	Colour rendering index	Lifetime	Weight
0000-003213.1100/830	1100 lm	12W	75 lm/W	3000K	80 Ra	50,000 h	2,55 kg
0000-003213.1100/840	1100 lm	11W	82 lm/W	4000K	80 Ra	50,000 h	2,55 kg
0000-003213.2000/830	2000 lm	22W	78 lm/W	3000K	80 Ra	50,000 h	2,55 kg
0000-003213.2000/840	2000 lm	20W	86 lm/W	4000K	80 Ra	50,000 h	2,55 kg
0000-003213.3000/830	3000 lm	34W	77 lm/W	3000K	80 Ra	50,000 h	2,55 kg
0000-003213.3000/840	3000 lm	32W	82 lm/W	4000K	80 Ra	50,000 h	2,55 kg

Touch & DALI ballast is also available - please add TD after index no.