


Wall mounted outdoor LED luminaire. Body is made of stainless steel and aluminum and it is available in all RAL colours. Light source - Philips Fortimo SLM or Osram PrevaLED module. Standard EVG ballast, Touch DALI version on request.



- IP54
- 230 V
50 Hz
- F
- ⏚
- CE



Index no.	Lumen output	Wattage	System efficacy	Colour temp.	Colour rendering index	Lifetime	Weight
0000-003667.1100/830	1100 lm	14W	69 lm/W	3000K	85 Ra	50,000 h	5,16 kg
0000-003667.1100/835	1100 lm	13W	74 lm/W	3500K	85 Ra	50,000 h	5,16 kg
0000-003667.1100/840	1100 lm	12W	80 lm/W	4000K	85 Ra	50,000 h	5,16 kg
0000-003667.2000/827	2000 lm	26W	69 lm/W	2700K	85 Ra	50,000 h	5,16 kg
0000-003667.2000/830	2000 lm	24W	74 lm/W	3000K	85 Ra	50,000 h	5,16 kg
0000-003667.2000/835	2000 lm	23W	77 lm/W	3500K	85 Ra	50,000 h	5,16 kg
0000-003667.2000/840	2000 lm	20W	86 lm/W	4000K	85 Ra	50,000 h	5,16 kg
0000-003667.2000/927	2000 lm	35W	52 lm/W	2700K	95 Ra	50,000 h	5,16 kg
0000-003667.2000/930	2000 lm	32W	57 lm/W	3000K	95 Ra	50,000 h	5,16 kg

