

Recessed downlight for compact fluorescent lamps. Body (standard zinc, painted black on request) and ring (standard white, other colours on request) are made of steel. Reflector made of aluminium.

Technical extras upon request:

1. Emergency supply  
- battery pack 1/2/3h (please add EM1, EM2 or EM3 after index number)
2. Compensation or passive power (capacitor).  
Please add COMPENSATION after index number.
3. Dimmable ballast EVG DIM (1-10 V).  
Please add EVG DIM after index number.
4. Digital dimmable ballast (DALI).  
Please add DALI after index number.


IP20

230 V  
50 Hz

CE



Easy installation  
- without  
tools.



Mounting  
brackets.



This downlight  
is available  
with remote  
gearbox only.

Index no.	Lamp	Weight	Socket
114.160.113V	VVG, 1x13W TC-D	1,10 kg	G24d - 1
114.160.113E	EVG, 1x13W TC-DEL	0,90 kg	G24q - 1
114.160.118V	VVG, 1x18W TC-D	1,10 kg	G24d - 2
114.160.118E	EVG, 1x18W TC-DEL	0,90 kg	G24q - 2
114.160.213V	VVG, 2x13W TC-D	1,30 kg	G24d - 1
114.160.213E	EVG, 2x13W TC-DEL	1,10 kg	G24q - 1
114.160.218V	VVG, 2x18W TC-D	1,30 kg	G24d - 2
114.160.218E	EVG, 2x18W TC-DEL	1,10 kg	G24q - 2

For decorative accessories see page 240

