


Recessed downlight for compact fluorescent lamps. Body (standard zinc, painted black on request) and ring (standard white, other colours on request) are made of steel. Reflector made of aluminium.



- IP20
- 230 V
50 Hz
- F
- ⏚
- CE

Technical extras upon request:

1. Emergency supply
- battery pack 1/2/3h (please add EM1, EM2 or EM3 after index number)
2. Compensation or passive power (capacitor).
Please add COMPENSATION after index number.
3. Dimmable ballast EVG DIM (1-10 V).
Please add EVG DIM after index number.
4. Digital dimmable ballast (DALI).
Please add DALI after index number.



Mounting brackets.

Index no.	Lamp	Weight	Socket
05.220.2716V	VVG, 1x13W TC-D	1,80 kg	G24d - 1
05.220.2716E	EVG, 1x13W TC-DEL	1,65 kg	G24q - 1
05.220.2717V	VVG, 1x18W TC-D	1,80 kg	G24d - 2
05.220.2717E	EVG, 1x18W TC-DEL	1,65 kg	G24q - 2
05.220.2720V	VVG, 1x26W TC-D	2,10 kg	G24d - 3
05.220.2720E	EVG, 1x26W TC-DEL	1,70 kg	G24q - 3
05.220.2718V	VVG, 2x13W TC-D	2,10 kg	G24d - 1
05.220.2718E	EVG, 2x13W TC-DEL	1,80 kg	G24q - 1
05.220.2719V	VVG, 2x18W TC-D	2,10 kg	G24d - 2
05.220.2719E	EVG, 2x18W TC-DEL	1,80 kg	G24q - 2
05.220.2721V	VVG, 2x26W TC-D	2,10 kg	G24d - 3
05.220.2721E	EVG, 2x26W TC-DEL	1,80 kg	G24q - 3

For decorative accessories see page 240

