

Recessed IP44 downlight for compact fluorescent lamp. Body is made of steel and aluminum and can be painted in all RAL colours on request. Reflector is made of aluminium.




Technical extras upon request:

1. Emergency supply
- battery pack 1/2/3h (please add EM1, EM2 or EM3 after index number)
2. Compensation or passive power (capacitor).
Please add COMPENSATION after index number.
3. Dimmable ballast EVG DIM (1-10 V).
Please add EVG DIM after index number.
4. Digital dimmable ballast (DALI).
Please add DALI after index number.



Easy installation – without tools.



Mounting brackets.



IP44 glass can be clear or mat.

All DLV 185 FG downlights are in standard with remote gearbox.

Index no.	Lamp	Weight	Socket
266.185.113V	VVG, 1x13W TC-D	1,60 kg	G24d - 1
266.185.113E	EVG, 1x13W TC-DEL	1,50 kg	G24q - 1
266.185.118V	VVG, 1x18W TC-D	1,60 kg	G24d - 2
266.185.118E	EVG, 1x18W TC-DEL	1,50 kg	G24q - 2
266.185.126V	VVG, 1x26W TC-D	1,60 kg	G24d - 3
266.185.126E	EVG, 1x26W TC-DEL	1,50 kg	G24q - 3

