

Recessed square downlight for compact fluorescent lamps. Body (standard zinc, painted black on request) and ring (standard white, other colours on request) are made of steel.



Technical extras upon request:

1. Emergency supply
- battery pack 1/2/3h (please add EM1, EM2 or EM3 after index number)
2. Compensation or passive power (capacitor).
Please add COMPENSATION after index number.
3. Dimmable ballast EVG DIM (1-10 V).
Please add EVG DIM after index number.
4. Digital dimmable ballast (DALI).
Please add DALI after index number.



Easy installation - without tools.



Mounting brackets.

Available decorative accessories:
- IP20 decorative glass (clear or mat)
- IP44 decorative glass (clear or mat)

All downlights are available with remote gearbox.
Please add RGB after index number

Index no.	Lamp	Weight	Socket
268.113V	VVG, 1x13W TC-T	1,25 kg	G24d - 1
268.113E	EVG, 1x13W TC-TEL	1,10 kg	G24q - 1
268.118V	VVG, 1x18W TC-T	1,25 kg	G24d - 2
268.118E	EVG, 1x18W TC-TEL	1,10 kg	G24q - 2
268.126V	VVG, 1x26W TC-T	1,35 kg	G24d - 3
268.126E	EVG, 1x26W TC-TEL	1,25 kg	G24q - 3

160 x 160

