

Surface mounted downlight for compact fluorescent lamps. Body is made of aluminium (standard white – available in any RAL colour on request).



Technical extras upon request:

1. Emergency supply  
- battery pack 1h  
- battery pack 2h  
Please add EM1, EM2 after index number.
2. Compensation or passive power (capacitor).  
Please add COMPENSATION after index number.
3. Dimmable ballast EVG DIM (1-10 V).  
Please add EVG DIM after index number.
4. Digital dimmable ballast (DALI).  
Please add DALI after index number.



Diamond faceted reflector.

Index no.	Lamp	Weight	Socket
DLN 220 with diamond faceted reflector.			
F26.220.6482V	VVG, 1x13W TC-D	1,60 kg	G24d - 1
F26.220.6482E	EVG, 1x13W TC-DEL	1,45 kg	G24q - 1
F26.220.6480V	VVG, 1x18W TC-D	1,60 kg	G24d - 2
F26.220.6480E	EVG, 1x18W TC-DEL	1,45 kg	G24q - 2
F26.220.6492V	VVG, 2x13W TC-D	1,90 kg	G24d - 1
F26.220.6492E	EVG, 2x13W TC-DEL	1,60 kg	G24q - 1
F26.220.6490V	VVG, 2x18W TC-D	1,90 kg	G24d - 2
F26.220.6490E	EVG, 2x18W TC-DEL	1,60 kg	G24q - 2
F26.220.6590V	VVG, 2x26W TC-D	2,00 kg	G24d - 3
F26.220.6590E	EVG, 2x26W TC-DEL	1,70 kg	G24q - 3

Index no.	Lamp	Weight	Socket
DLN 220 with plain glossy reflector.			
G26.220.6482V	VVG, 1x13W TC-D	1,60 kg	G24d - 1
G26.220.6482E	EVG, 1x13W TC-DEL	1,45 kg	G24q - 1
G26.220.6480V	VVG, 1x18W TC-D	1,60 kg	G24d - 2
G26.220.6480E	EVG, 1x18W TC-DEL	1,45 kg	G24q - 2
G26.220.6492V	VVG, 2x13W TC-D	1,90 kg	G24d - 1
G26.220.6492E	EVG, 2x13W TC-DEL	1,60 kg	G24q - 1
G26.220.6490V	VVG, 2x18W TC-D	1,90 kg	G24d - 2
G26.220.6490E	EVG, 2x18W TC-DEL	1,60 kg	G24q - 2
G26.220.6590E	EVG, 2x26W TC-DEL	1,70 kg	G24q - 3
G26.220.6590V	VVG, 2x26W TC-D	2,00 kg	G24d - 3

For decorative accessories see page 240.

