

Surface mounted downlight for compact fluorescent lamps with IP44 flat glass. Body is made of aluminium (standard white – available in any RAL colour on request).



IP44

230 V  
50 Hz

CE

Technical extras upon request:

1. Compensation or passive power (capacitor).  
Please add COMPENSATION after index number.

2. Dimmable ballast EVG DIM (1-10 V).  
Please add EVG DIM after index number.

3. Digital dimmable ballast (DALI).  
Please add DALI after index number.



| Index no.     | Lamp              | Weight  | Socket   |
|---------------|-------------------|---------|----------|
| 275.220.6482V | VVG, 1x13W TC-D   | 1,40 kg | G24d - 1 |
| 275.220.6482E | EVG, 1x13W TC-DEL | 1,25 kg | G24q - 1 |
| 275.220.6480V | VVG, 1x18W TC-D   | 1,40 kg | G24d - 2 |
| 275.220.6480E | EVG, 1x18W TC-DEL | 1,25 kg | G24q - 2 |
| 275.220.6492V | VVG, 2x13W TC-D   | 1,70 kg | G24d - 1 |
| 275.220.6492E | EVG, 2x13W TC-DEL | 1,40 kg | G24q - 1 |
| 275.220.6490V | VVG, 2x18W TC-D   | 1,70 kg | G24d - 2 |
| 275.220.6490E | EVG, 2x18W TC-DEL | 1,40 kg | G24q - 2 |
| 275.220.6590V | VVG, 2x26W TC-D   | 1,80 kg | G24d - 3 |
| 275.220.6590E | EVG, 2x26W TC-DEL | 1,50 kg | G24q - 3 |

