

Recessed IP54 downlight for metal halide light source. Body is made of aluminium - ring available in different RAL colours. Two versions are available - with low or high ring.

IP54


230 V  
50 Hz



CE



Easy installation – without tools.



Mounting brackets.



DL GOT 170 H - high ring



## DL GOT 170 L

Index no.	Lamp	Weight	Socket
103.170.35V	VVG, 1x35W CDM-T	2,50 kg	G12
103.170.35E	EVG, 1x35W CDM-T	1,45 kg	G12
103.170.70V	VVG, 1x70W CDM-T	2,50 kg	G12
103.170.70E	EVG, 1x70W CDM-T	1,45 kg	G12
103.170.150V	VVG, 1x150W CDM-T	3,90 kg	G12
103.170.150E	EVG, 1x150W CDM-T	2,30 kg	G12

## DL GOT 170 H

Index no.	Lamp	Weight	Socket
104.170.35V	VVG, 1x35W CDM-T	2,55 kg	G12
104.170.35E	EVG, 1x35W CDM-T	1,50 kg	G12
104.170.70V	VVG, 1x70W CDM-T	2,55 kg	G12
104.170.70E	EVG, 1x70W CDM-T	1,50 kg	G12
104.170.150V	VVG, 1x150W CDM-T	3,95 kg	G12
104.170.150E	EVG, 1x150W CDM-T	2,35 kg	G12

