

# DL 220 LED CB



Recessed LED luminaires.

Body is made of steel and aluminium and it is available in all RAL colours.

Light source - Osram PrevaLED cube.


Standard EVG ballast, DALI version on request.

Optional IP44 ring with clear or mat glass (please add -0021/1 after index number).

High quality, energy efficient white LED light with CRI 80.

Perfect replacement for CFL downlights in:

- Offices
- Public buildings
- Hotel lobbies and receptions
- Retail



Index no.	Lumen output	Wattage	Colour temp.	Colour rendering index	Lifetime	Weight
With integrated AC driver						
0000-004531.1100/830	1100 lm	14 W	3000 K	80 Ra	50,000 h	1,50 kg
0000-004531.1100/840	1100 lm	13 W	4000 K	80 Ra	50,000 h	1,50 kg
0000-004531.2000/830	2000 lm	28 W	3000 K	80 Ra	50,000 h	1,50 kg
0000-004531.2000/840	2000 lm	26 W	4000 K	80 Ra	50,000 h	1,50 kg
0000-004531.3000/830	3000 lm	43 W	3000 K	80 Ra	50,000 h	1,50 kg
0000-004531.3000/840	3000 lm	39 W	4000 K	80 Ra	50,000 h	1,50 kg
With AC/DC driver						
0000-004532.1100/840	1100 lm	12 W	3000 K	80 Ra	50,000 h	2,10 kg
0000-004532.1100/840	1100 lm	12 W	4000 K	80 Ra	50,000 h	2,10 kg
0000-004532.2000/830	2000 lm	20 W	3000 K	80 Ra	50,000 h	2,10 kg
0000-004532.2000/840	2000 lm	20 W	4000 K	80 Ra	50,000 h	2,10 kg
0000-004532.3000/830	3000 lm	30 W	3000 K	80 Ra	50,000 h	2,10 kg
0000-004532.3000/840	3000 lm	30 W	4000 K	80 Ra	50,000 h	2,10 kg

IP20

230 V  
50 Hz



CE

