

# DL 185 LED CB



Recessed LED luminaire.

Body is made of steel and aluminium and it is available in all RAL colours.

Light source - Osram PrevaLED cube.


Standard EVG ballast, DALI version on request.

Optional IP44 ring with clear or mat glass (please add -0021/1 after index number).

High quality, energy efficient white LED light with CRI 80.

Perfect replacement for CFL downlights in:

- Offices
- Public buildings
- Hotel lobbies and receptions
- Retail



| Index no.                 | Lumen output | Wattage | Colour temp. | Colour rendering index | Lifetime | Weight  |
|---------------------------|--------------|---------|--------------|------------------------|----------|---------|
| With integrated AC driver |              |         |              |                        |          |         |
| 0000-004573.1100/830      | 1100 lm      | 14 W    | 3000 K       | 80 Ra                  | 50,000 h | 1,40 kg |
| 0000-004573.1100/840      | 1100 lm      | 13 W    | 4000 K       | 80 Ra                  | 50,000 h | 1,40 kg |
| 0000-004573.2000/830      | 2000 lm      | 28 W    | 3000 K       | 80 Ra                  | 50,000 h | 1,40 kg |
| 0000-004573.2000/840      | 2000 lm      | 26 W    | 4000 K       | 80 Ra                  | 50,000 h | 1,40 kg |
| 0000-004573.3000/830      | 3000 lm      | 43 W    | 3000 K       | 80 Ra                  | 50,000 h | 1,40 kg |
| 0000-004573.3000/840      | 3000 lm      | 39 W    | 4000 K       | 80 Ra                  | 50,000 h | 1,40 kg |
| With AC/DC driver         |              |         |              |                        |          |         |
| 0000-004500.1100/830      | 1100 lm      | 12 W    | 3000 K       | 80 Ra                  | 50,000 h | 2,00 kg |
| 0000-004500.1100/840      | 1100 lm      | 12 W    | 4000 K       | 80 Ra                  | 50,000 h | 2,00 kg |
| 0000-004500.2000/830      | 2000 lm      | 20 W    | 3000 K       | 80 Ra                  | 50,000 h | 2,00 kg |
| 0000-004500.2000/840      | 2000 lm      | 20 W    | 4000 K       | 80 Ra                  | 50,000 h | 2,00 kg |
| 0000-004500.3000/830      | 3000 lm      | 30 W    | 3000 K       | 80 Ra                  | 50,000 h | 2,00 kg |
| 0000-004500.3000/840      | 3000 lm      | 30 W    | 4000 K       | 80 Ra                  | 50,000 h | 2,00 kg |

IP20

230 V  
50 Hz

