

ATLANTYK STRONG LED

GARRABRIDGE

Industrial luminaire for LED light sources, water-jet protected with an increased chemical resistance, dedicated to use in extreme environments.



Body: polyester material reinforced with fibreglass

Type of diffuser: opal acrylic

Additional elements: stainless steel clips

Colour: gray

Way of mounting: directly on the ceiling or suspended using hooks (included)

Applications:

Parking lots, heavy and chemical industries, bakeries, restaurant kitchens, butchers', swimming pools, outdoor roofings, production halls, power plants



Code	Emergency kit	Lumen LED [lm] ¹⁾	Lumen luminaire [lm] ¹⁾	Color temperature [K]	Colour Rendering Index [CRI]	Power LED [W]	Luminaire power [W]	Wymiary [mm] L W H D	Weight [kg]
090250.5L01.711	+	3550	3200	4000	>80	29	32	1299 85 92 700	1,7
090250.5L03.711	+	4400	3900	4000	>80	33	35	1299 85 92 700	1,7
090250.5L04.711	+	5300	4700	4000	>80	42	45	1299 85 92 700	1,7
090250.5L05.711	+	7400	6640	4000	>80	57	61	1299 85 92 700	1,7
090250.5L06.711	+	2950	2650	3000	>80	25	28	1299 85 92 700	1,7
090250.5L08.711	+	4200	3650	3000	>80	33	35	1299 85 92 700	1,7
090250.5L09.711	+	5100	4500	3000	>80	42	45	1299 85 92 700	1,7
090250.5L10.711	+	7100	6380	3000	>80	57	61	1299 85 92 700	1,7
radar motion detector									
090250.5L01.711.920	-	3550	3200	4000	>80	29	32	1299 85 92 700	1,7
090250.5L03.711.920	-	4400	3900	4000	>80	33	36	1299 85 92 700	1,7
090250.5L04.711.920	-	5300	4700	4000	>80	42	46	1299 85 92 700	1,7
090250.5L05.711.920	-	7400	6640	4000	>80	57	62	1299 85 92 700	1,7
090250.5L06.711.920	-	2950	2650	3000	>80	25	29	1299 85 92 700	1,7
090250.5L08.711.920	-	4200	3650	3000	>80	33	36	1299 85 92 700	1,7
090250.5L09.711.920	-	5100	4500	3000	>80	42	46	1299 85 92 700	1,7
090250.5L10.711.920	-	7100	6380	3000	>80	57	62	1299 85 92 700	1,7

¹⁾ Luminous flux tolerance + / - 10%

