

Robust cornice mounted enclosed luminaire with white texture paint finish as standard, RAL colours optional. Two body dimensions available, standard & slim versions (see dimensions below). Bezel/Diffuser removes without disturbing anti pick mastic. LED versions available on request & long life fluorescent versions.

- IP65 - IK10 ++
- Fully Welded Fabricated Steel Body
- Optional VANDACOAT offering enhanced Corrosion/Vandal & Graffiti Resistant Coating System
- Regressed Gasketed Bezel
- Captive 6mm Opal or Clear Stippled Polycarbonate Diffuser
- Stainless Steel Torx Security Screw Fixing
- Removable High Frequency Gear Tray
- Other RAL colour options
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Option

Applications:

Corridors, Warehouses, Covered Walk Ways, Schools, Hospitals, Prisons, Police Stations, Public Areas, Underpass Walkways, etc.



RANGE AVAILABLE

Index No.	Description	Length	Weight
COR114	1x14W HF T5	2ft / 660mm	6,0 kg
COR124	1x24W HF T5	2ft / 660mm	6,0 kg
COR128	1x28W HF T5	4ft / 1260mm	9,0 kg
COR154	1x54W HF T5	4ft / 1260mm	9,0 kg
COR135	1x35W HF T5	5ft / 1560mm	10,0 kg
COR149	1x49W HF T5	5ft / 1560mm	10,0 kg
COR214	2x14W HF T5	2ft / 660mm	6,0 kg
COR224	2x24W HF T5	2ft / 660mm	6,0 kg
COR228	2x28W HF T5	4ft / 1260mm	9,0 kg
COR254	2x54W HF T5	4ft / 1260mm	9,0 kg
COR235	2x35W HF T5	5ft / 1560mm	10,0 kg
COR249	2x49W HF T5	5ft / 1560mm	10,0 kg

Suffix

/SLM	Slim Body Dimension
/60°/30°	Slim Body Dimension
/SKI 60°	60° Ski Sloping Top Version
/P	Clear Stippled Diffuser
/O	Opal Diffuser
/HFD	High Frequency Dimmable
/NL	Night Light
/EM3	3 hour maintained Emergency
/SD	Security Driver
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option
/VCOTE	VANDACOAT Enhanced External Coating System

LED VERSIONS

Wattage p/mtr	No LED's	Voltage	Lms	Weight
Compromising of 10 qty x 100mm sections of 2.3W				
COR23wLED	60	24V/240V	2100 per lampway	8,0 kg
Various T5/T8 type LED Tubes on request				
Available in colour temp 3000/4000/5000K				

*Stainless Steel version for special applications

