

Robust recessed mounted enclosed luminaire with white paint finish. Traditional ceiling construction supplied c/w 4 x No adjustable side arm suspension brackets. Underside body rated IP65. Bezel/Diffuser removes without disturbing anti pick mastic. LED & long life fluorescent options.

**Anti Ligature** note: When correctly installed against ceiling, using 'Anti Pick' Mastic

- IP65 - IK10 ++
- Steel Body Powder Coated White
- Suitable for Concealed or Exposed Grid Ceilings
- Fully Gasketed Regressed Frame (which removes without disturbing anti-pick mastic)
- Captive Polycarbonate Diffuser
- Clear Stippled or Opal Panel
- Stainless Steel Security Screws
- Removable High Frequency Gear Tray
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Option

**Applications:**

Prisons, Police Stations, Detention Centres, Hospitals, Schools, Secure Units, Kitchens, Laboratories, Clean Rooms, etc.



**RANGE AVAILABLE**

Index No.	Description	Dimension	Weight
SEC214	2x14W HF T5	600mm x 300mm	6.0 kg
SEC224	2x24W HF T5	600mm x 300mm	6.0 kg
SEC314	3x14W HF T5	600mm x 600mm	10,0 kg
SEC414	4x14W HF T5	600mm x 600mm	10,0 kg
SEC228	2x28W HF T5	1200mm x 300mm	9,0 kg
SEC224	2x54W HF T5	1200mm x 300mm	9,0 kg
SEC328	3x28W HF T5	1200mm x 600mm	14,0 kg
SEC428	4x28W HF T5	1200mm x 600mm	14,0 kg
SEC354	3x54W HF T5	1200mm x 600mm	14,0 kg
SEC454	4x54W HF T5	1200mm x 600mm	14,0 kg

**Suffix**

/P	Clear Obscure Diffuser
/O	Opal Diffuser
/HFD	High Frequency Dimmable Gear
/EM3	3 Hour Maintained Emergency
/NL	9 Watt Night Light
/SS	Stainless Steel Security Screws
/SD	Security Driver
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option

**LED VERSIONS**

Wattage p/mtr	No LED's	Voltage	Lms
Compromising of 10 qty x 100mm sections of 2.3W			
SEC23wLED	60	24V/240V	2100 per lampway

LED flat panel on request  
 Various T5/T8 type LED Tubes on request  
 Available in colour temp 3000/4000/5000K

\*Stainless Steel version available for special applications

