



RANGE AVAILABLE

Index No.	Description	Length	Weight
GARV114	1x14W HF T5	2ft / 650mm	6,0 kg
GARV124	1x24W HF T5	2ft / 650mm	6,0 kg
GARV128	1x28W HF T5	4ft / 1250mm	9,0 kg
GARV154	1x54W HF T5	4ft / 1250mm	9,0 kg
GARV135	1x35W HF T5	5ft / 1550mm	10,0 kg
GARV149	1x49W HF T5	5ft / 1550mm	10,0 kg
GARV214	2x14W HF T5	2ft / 650mm	6,0 kg
GARV224	2x24W HF T5	2ft / 650mm	6,0 kg
GARV228	2x28W HF T5	4ft / 1250mm	9,0 kg
GARV254	2x54W HF T5	4ft / 1250mm	9,0 kg
GARV235	2x35W HF T5	5ft / 1550mm	10,0 kg
GARV249	2x49W HF T5	5ft / 1550mm	10,0 kg

LED VERSIONS

Wattage p/mtr	No LED's	Voltage	Lms	Weight
Compromising of 10 qty x 100mm sections of 2.3W				
GARV23wLED	60	24V/240V	2100 per lampway	8,0 kg
Various T5/T8 type LED Tubes on request				
Available in colour temp 3000/4000/5000K				

*Stainless Steel version for special applications

Suffix

/HFD	High Frequency Dimmable
/P	Clear Stippled Diffuser
/O	Opal Diffuser
/HFD	High Frequency Dimmable
/EM3	Integral 3 hour Emergency
/NL	9W Night Light
/SD	Security Key
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option
/VCOTE	VANDACOAT Enhanced External Coating System

Slim robust surface mounted enclosed luminaire, anti-ligature construction (when installed correctly) with texture white paint finish as standard. Bezel/ Diffuser removes without disturbing anti pick mastic. LED versions available on request.

Anti Ligature note: When correctly installed against ceiling, using 'Anti Pick' Mastic.

- IP65 - IK10 ++
- Fully Welded Fabricated Steel Body
- Optional VANDACOAT offering enhanced Corrosion/Vandal & Graffiti Resistant Coating System
- Regressed Gasketed Bezel, Captive Polycarb Panel
- Torx Security Screw Fixing
- Removable High Frequency Gear Tray
- Other RAL colour options
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Option

Applications:

Prisons, Police Stations, Detention Centres, Public Spaces, Psychiatric Hospitals, Schools etc

