

# LIBERTY INDIRECT

## RECESSED MODULAR

A range of recessed modular fluorescent luminaires is suitable for applications where aesthetic appearance and light control are important, with central curved perforated metal diffuser. LED option on request & long life fluorescent options.

- IP20
- Central Curved Perforated Metal Diffuser
- Indirect Lighting Control
- Powder Coated Paint Finish
- Suitable for 15/25 Exposed 'T' Grid Ceilings
- Optional Extra Bezel for Plasterboard Ceilings
- High Frequency Control Gear
- Microwave Motion Detection Option
- Longlife 50,000 hrs Fluorescent options
- LED Option

### Applications:

Commercial Office Lighting, Meeting Rooms, Computer Rooms, Retail Areas, Reception, Medical Areas, etc.



### RANGE AVAILABLE

Index No.	Description	Weight
LIBI236	2 x 36W TC-L	4,3 kg
LIBI240	2 x 40W TC-L	4,3 kg
LIBI255	2 x 55W TC-L	4,3 kg

### LED VERSIONS

Wattage p/mtr	No LED's	Voltage	Lms	Weight
Compromising of 10 qty x 100mm sections of 2.3W				
LIBI23wLED	60	24V/240V	2100 per lampway	4,3 kg

Various T5/T8 type LED Tubes on request  
Available in colour temp 3000/4000/5000K

### Suffix

/HFD	High Frequency Dimmable Gear
/EM3	3 Hour Maintained Emergency
/ATT	Plasterboard Mounting Kit
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option

