


Professional streetlight luminaire for LED light sources.



Body: high pressure die-cast aluminum
Type of diffuser: tempered glass
Colour: gray
Way of mounting: on pillars or outriggers

Applications:
 National roads, municipal, back roads, roads in residential areas, local, car parks, roundabouts, bicycle lanes, industrial areas, residential areas



Code	HF DALI	Lumen LED [lm] ¹⁾	Lumen luminaire [lm] ¹⁾	Color temperature [K]	Colour Rendering Index [CRI]	Power LED [W]	Luminaire power [W]	Wymiary [mm] L W H	Weight [kg]
LLOC									
130182.PL011.11	²⁾	3750	2900	4000	>80	33	35	490 240 170	4,2
130182.PL021.12	²⁾	7500	5850	4000	>80	66	70	645 240 170	6,8
130182.PL031.12	²⁾	9350	7300	4000	>80	82	90	645 240 170	6,8
130182.PL041.11	²⁾	4300	3350	5700	>70	33	35	490 240 170	4,2
130182.PL051.12	²⁾	8650	6700	5700	>70	66	70	645 240 170	6,8
130182.PL061.12	²⁾	10800	8400	5700	>70	82	90	645 240 170	6,8
130182.PL071.11	²⁾	4300	3350	6500	>65	33	35	490 240 170	4,2
130182.PL081.12	²⁾	8650	6700	6500	>65	66	70	645 240 170	6,8
130182.PL091.12	²⁾	10800	8400	6500	>65	82	90	645 240 170	6,8
ED									
130182.5L011.11	-	3750	2900	4000	>80	33	35	490 240 170	4,2
130182.5L041.11	-	4300	3350	5700	>70	33	35	490 240 170	4,2
130182.5L071.11	-	4300	3350	6500	>65	33	35	490 240 170	4,2

¹⁾ Luminous flux tolerance + / - 10%

²⁾ When ordering DALI version of the index should add .968

