


Professional streetlight luminaire for LED light sources.



Body: high pressure die-cast aluminum
Type of diffuser: tempered glass
Colour: gray, graphite
Way of mounting: on pillars or outriggers with a diameter of 60mm and 76mm

Applications:
 Illumination of motorways; main, secondary and local roads, industrial areas, residential districts, car parks, shopping centers.



Code	Power LED [W]	Luminaire power [W]	Lumen LED [lm] ¹⁾	Lumen luminaire [lm] ¹⁾	Colour temperature [K]	CRI [Ra]	Dimensions [mm] L W H	Weight [kg]
130192.5L05.11	94	100	13100	10800	4000	>70	730 135 295	10,2
130192.5L06.11	94	100	13100	10800	5700	>70	730 135 295	10,2
130192.5L07.11	94	100	14200	11600	6500	>70	730 135 295	10,2
130195.5L05.11	94	100	13100	10800	4000	>70	730 135 295	10,2
130195.5L06.11	94	100	13100	10800	5700	>70	730 135 295	10,2
130195.5L07.11	94	100	14200	11600	6500	>70	730 135 295	10,2
130192.5L08.11	144	155	19700	16200	4000	>70	730 135 295	10,4
130192.5L09.11	144	155	19700	16200	5700	>70	730 135 295	10,4
130192.5L10.11	144	155	21300	17500	6500	>70	730 135 295	10,4
130195.5L08.11	144	155	19700	16200	4000	>70	730 135 295	10,4
130195.5L09.11	144	155	19700	16200	5700	>70	730 135 295	10,4
130195.5L10.11	144	155	21300	17500	6500	>70	730 135 295	10,4

¹⁾ Luminous flux tolerance +/- 10%

