

METROPOLITAN RAIL LED

SECTION 12 COMPLIANT VANDAL RESISTANT RANGE



Robust surface/recessed mounted enclosed luminaire section 12 compliant c/w toughened glass panel, low smoke & zero halogen cables / control gear c/w Special gasket.

*Stainless steel version for special applications.

- IK10++ - IP65
- Fully Welded Fabricated Steel Body
- Optional Vandacoat Offering Enhanced Corrosion/Vandal & Graffiti Resistant Coating System
- Regressed Gasketed Bezel
- Captive Toughened Glass Diffuser
- Torx Security Screw Fixing
- Other RAL Colour Options
- Microwave Motion Detection Option

Applications:

Underground and Railway Applications.



LED VERSIONS

Wattage	Description	T5 Equivalent	Dimensions
MET10wLED	10 watt / 1300lm LED Strip	1 x 14w T5	2ft / 650mm
MET15wLED	15 watt / 1950lm LED Strip	1 x 21w T5	3ft / 950mm
MET16wLED	16 watt / 2080lm LED Strip	1 x 24w T5	2ft / 650mm
MET20wLED	20 watt / 2600lm LED Strip	1 x 28w T5	4ft / 1250mm
MET25wLED	25 watt / 3250lm LED Strip	1 x 35w T5	5ft / 1550mm
MET26wLED	26 watt / 3380lm LED Strip	1 x 39w T5	3ft / 950mm
MET34wLED	34 watt / 4420lm LED Strip	1 x 49w T5	5ft / 1550mm
MET38wLED	38 watt / 4940lm LED Strip	1 x 54w T5	4ft / 1250mm
MET20wLED	20 watt / 2600lm LED Strip	2 x 14w T5	2ft / 650mm
MET30wLED	30 watt / 3900lm LED Strip	2 x 21w T5	3ft / 950mm
MET32wLED	32 watt / 4160lm LED Strip	2 x 24w T5	2ft / 650mm
MET40wLED	40 watt / 5200lm LED Strip	2 x 28w T5	4ft / 1250mm
MET50wLED	50 watt / 6500lm LED Strip	2 x 35w T5	5ft / 1550mm
MET52wLED	52 watt / 6760lm LED Strip	2 x 39w T5	3ft / 950mm
MET68wLED	68 watt / 8840lm LED Strip	2 x 49w T5	5ft / 1550mm
MET76wLED	76 watt / 9880lm LED Strip	2 x 54w T5	4ft / 1250mm

Suffix

/FSP	Flat Frosted Seamless Poly Diffuser
/W	White Finish
/S	Silver Finish
/SS	Fitted with Security Screws
/SD	Security Screwdriver
/M-WAVE	Microwave Motion Detection
/EYE	Eyelid Option
/VCOAT	Vandacoat (Enhanced Corrosion/Vandal & Graffiti Resistant Coating)

