

PLATOON RAIL LED

SECTION 12 COMPLIANT VANDAL RESISTANT RANGE



Robust surface/recessed mounted enclosed luminaire section 12 compliant c/w toughened glass panel, low smoke & zero halogen cables / control gear c/w special gasket.

*Stainless steel version for special applications.

- IK10++ - IP65
- Fully Welded Fabricated Steel Body
- Optional Vandacoat Offering Enhanced Corrosion/Vandal & Graffiti Resistant Coating System
- Regressed Gasketed Bezel
- Captive Toughened Glass Diffuser
- Torx Security Screw Fixing
- Other RAL Colour Options
- Microwave Motion Detection Option

Applications:
Underground and Railway Applications.



LED VERSIONS

Wattage	Description	CFL Equivalent
PLA10wLED	10 watt / 1100lm LED Array	16w 2D HF TC-DD
PLA26wLED	26 watt / 2860lm LED Array	2 x 26w PL HF
PLA16wLED	16 watt / 1760lm LED Array	28w 2D HF TC-DD
PLA21wLED	21 watt / 2310lm LED Array	38w 2D HF TC-DD

Suffix

/FSP	Flat Frosted Seamless Poly Diffuser
/W	White Finish
/S	Silver Finish
/SS	Fitted with Security Screws
/SD	Security Screwdriver
/M-WAVE	Microwave Motion Detection
/EYE	Eyelid Option
/VCOAT	Vandacoat (Enhanced Corrosion/Vandal & Graffiti Resistant Coating)

