


Industrial luminaire for LED light sources

**TECHNICAL DATA:**

- Mounting:** suspended, on chains (on request), manufacturer does not provide suspension components
- Body:** high pressure die-cast aluminum
- Colour:** gray
- Diffuser:** tempered glass

**ELECTRICAL DATA:**

- Power supply efficiency:** >95%
- Electrical connection:** 3-pole connector
- Power:** 220-240V 50/60Hz
- Includes light source:** yes
- Type of equipment:** ED, DALI



**OPTICAL DATA:**



- Light distribution:** rotationally-asymmetric
- Way of lighting:** direct

**ADDITIONAL INFO:** Ball impact resistance

- Lifetime (L70B50):** 60 000 h
- Lifetime (L80B10):** 50 000 h
- Lifetime (TM21 L90B10):** 40 000 h

**GENERAL DATA:**

- Warranty:** 3 years
- Application:** warehouses, logistics centers, industrial facilities, sport facilities, roofing, outdoor installation without roof on special request (index extension: .985)



300092.00067.985

Type of luminaires  
985 Luminaires for outdoor installation without roof on special request


- CE
- ERC
- F
- D
- 220-240V 50/60 Hz
- IK 07
- IP 66
- LED

Code	Dimensions [mm] L W H	Mounting dimensions [mm] L	Pallet quantity	Quantity in package	Net weight [kg]
<b>Type of equipment: ED</b>					
300092.00067	515 345 90	430	30	1	6.5
300092.00052	515 345 90	430	30	1	6.5
300092.00051	515 345 90	430	30	1	6.5
<b>Type of equipment: DALI</b>					
300092.00091	515 345 90	430	30	1	6.5
300092.00092	515 345 90	430	30	1	6.5
300092.00093	515 345 90	430	30	1	6.5


Code	Replacement of conventional technology [W]	Beam angle	Power LED [W]	Luminaire power [W]	Lumen LED [lm]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/ Ra	Operating temperature range [°C]
<b>Type of equipment: ED</b>										
300092.00067	150W MH (180W)	100°	100	111	14500	13600	123	4000	≥80	-30 ... +35
300092.00052	250W MH (300W)	100°	145	159	21000	19800	125	4000	≥80	-30 ... +40
300092.00051	250W MH (300W)	100°	177	194	25500	23800	123	4000	≥80	-30 ... +40
<b>Type of equipment: DALI</b>										
300092.00091	150W MH (180W)	100°	100	107	14500	13600	127	4000	≥80	-30 ... +45
300092.00092	250W MH (300W)	100°	145	156	21000	19800	127	4000	≥80	-30 ... +45
300092.00093	250W MH (300W)	100°	177	192	25500	23800	124	4000	≥80	-30 ... +40

**LIGHT BEAM CURVES**

300092.00067



300092.00052



300092.00051

