

WALL LED SPOT



IP20

230 V
50 Hz



CE



Wall mounted LED luminaire. Body is made of steel and aluminium and it is available in all RAL colours. Light source - Philips Fortimo SLM or Osram PrevaLED module. Standard EVG ballast, Touch DALI version on request.

High quality, energy efficient white LED light with CRI 80 and more.

Perfect replacement for conventional luminaires in:

- Offices
- Public buildings
- Hotel lobbies and receptions
- Retail



Index no.	Lumen output	Wattage	System efficacy	Colour temp.	Colour rendering index	Lifetime	Weight
0000-003496.1100/830	1100 lm	14W	69 lm/W	3000K	85 Ra	50,000 h	2,50 kg
0000-003496.1100/835	1100 lm	13W	74 lm/W	3500K	85 Ra	50,000 h	2,50 kg
0000-003496.1100/840	1100 lm	12W	80 lm/W	4000K	85 Ra	50,000 h	2,50 kg
0000-003496.2000/827	2000 lm	26W	69 lm/W	2700K	85 Ra	50,000 h	2,50 kg
0000-003496.2000/830	2000 lm	24W	74 lm/W	3000K	85 Ra	50,000 h	2,50 kg
0000-003496.2000/835	2000 lm	23W	77 lm/W	3500K	85 Ra	50,000 h	2,50 kg
0000-003496.2000/840	2000 lm	20W	86 lm/W	4000K	85 Ra	50,000 h	2,50 kg
0000-003496.2000/927	2000 lm	35W	52 lm/W	2700K	95 Ra	50,000 h	2,50 kg
0000-003496.2000/930	2000 lm	32W	57 lm/W	3000K	95 Ra	50,000 h	2,50 kg
0000-003496.3000/827	3000 lm	42W	64 lm/W	2700K	85 Ra	50,000 h	2,50 kg
0000-003496.3000/830	3000 lm	39W	69 lm/W	3000K	85 Ra	50,000 h	2,50 kg
0000-003496.3000/835	3000 lm	40W	68 lm/W	3500K	85 Ra	50,000 h	2,50 kg
0000-003496.3000/840	3000 lm	36W	75 lm/W	4000K	85 Ra	50,000 h	2,50 kg

Touch & DALI ballast is also available - please add TD after index no.

